



ESSELMANN

THE FT5.

THE NEW COOLING TRAILER.

THE NEW PRICE-PERFORMANCE REFERENCE.



corresponds
to ATP standard
level „IN“

Also
available as
FT4
more payload
at more compact
dimensions

AS STANDARD WITH:

- ✓ **SPLITCHILL®** cooling, the easy-to-maintain and repair-friendly refrigeration unit, with electronic refrigeration control and electric defrost heating
- ✓ rear entry step
- ✓ stable stainless steel rear portal with full loading width
- ✓ ESSELMANN **FePur®** isothermal body with robust anodised aluminium profiles and manoeuvring handles
- ✓ including registration documents **[CoC paper]**
- ✓ Space for five Euro pallets (1,200x800mm)

OPTIONALLY AVAILABLE:

- ESSELMANN **SPLITCHILL®** refrigeration unit in performance-enhanced tropical version for use at up to 43°C outside temperature at 40% higher cooling capacity
- load securing with lock bars
- LED vehicle lighting
- Lettering in digital print full foiling on sides and rear
- 100 km/h preparation
- Height-adjustable draw gear
- synthetic floor coating and lateral ram protection made of anodised aluminium checker plate

	FT5	FT4
Overall outer dimensions (LxWxH)	5,250x2,450x2,610mm	4,950x2,450x2,610mm
Interior body dimensions (LxWxH)	3,400x1,820x1,940mm	3,100x1,820x1,940mm
Empty weight approx.	1,040kg	1,000kg
Perm. gross weight	2,700kg	2,700kg
Payload in transport approx.	1,660kg	1,700kg
Payload in operation approx.	6,000kg	6,000kg



ESSELMANN

Robust. Flush stainless steel rear portal with reinforced corners. Extra sturdy, durable, and recoil-free.

1

Digital. Electronic refrigeration control and electric defrost heating.

2

Wide. Trailer with 1,820 mm interior width. Sufficient space even with beverage crates that are not euro-pallet compliant.

3

Smart. The boarding aid at the rear makes it easier to enter the trailer.

4

Practical. Anodised aluminium bodywork profiles with manoeuvring handles.



LED vehicle lighting.

More safety due to the bright and long-lasting LED lighting. No change of illuminant.



Synthetic floor coating. As a wear-resistant, slip-proof and absolutely leak-proof surface coating.

Impact protection made of anodised aluminium checker plate. On the inside walls of the box and rear door(s) approx. 1,200mm high, all-round



Bumper protection made of stainless steel sheet.

for outline, marker and rear lights.



Full-surface digital print lettering.

Stand out and label your trailer expressively.



COOLING UNIT IN TROPICAL VERSION UP TO 43°C

Be prepared for persistent summer heat and use the high-performance cooling units in tropical version.



100

100 km/h preparation

A more stable ride, thanks to 100 km/h preparation.